

# SuperSnake GTX - subfeeder



## BENEFITS

- Connects with Euro-connected welding guns
- Compatible with all X5 FastMig wire feed units featuring sub feeder synchronization
- 10-,15-, 20- and 25-meter water and gas-cooled models
- Suitable for 1.0mm to 1.6mm Fe/Ss/Al/FC/MC filler wires
- Easy parameter adjustment close at hand
- Clear meter display in all light conditions
- Safe lock switch prevents accidental activation
- LED cabinet lighting makes wire change and maintenance easy

## OVERVIEW

SuperSnake GTX subfeeder provides a simple and effective distance wire feeding solution up to 30m from the wire feed unit. Compatible with X5 FastMig wire feeders and standard Euro-connected MIG welding guns.

## TECHNICAL SPECIFICATIONS

### SuperSnake GTX - subfeeder

Product code	<p><b>Packages</b></p> <p>SuperSnake GTX GAS 10m package, 50mm<sup>2</sup>: P400GTX          SuperSnake GTX GAS 15m package, 50mm<sup>2</sup>: P401GTX          SuperSnake GTX GAS 20m package, 50mm<sup>2</sup>: P402GTX          SuperSnake GTX GAS 25m package, 50mm<sup>2</sup>: P403GTX          SuperSnake GTX WATER 10m package, 50mm<sup>2</sup>: P404GTX          SuperSnake GTX WATER 15m package, 50mm<sup>2</sup>: P405GTX          SuperSnake GTX WATER 20m package, 50mm<sup>2</sup>: P406GTX          SuperSnake GTX WATER 25m package, 50mm<sup>2</sup>: P407GTX          SuperSnake GTX WATER 10m package, 70mm<sup>2</sup>: P408GTX          All packages include SuperSnake GTX motor drive unit and frame (SGTXMDUPF01) and cable</p> <p><b>Other</b></p> <p>SuperSnake GTX motor drive unit: SGTXMDU01          SuperSnake GTX protection frame: SGTXPF01          SuperSnake GTX motor drive unit and frame: SGTXMDUPF01          SuperSnake Kit X5 Feeder: X5702030000</p> <p><b>Cables</b></p> <p>SuperSnake GTXG 10m cable, 50mm<sup>2</sup> (Std liner FE 1.0-1.6mm): SGTXG105CBL          SuperSnake GTXG 15m cable, 50mm<sup>2</sup> (Std liner FE 1.0-1.6mm): SGTXG155CBL          SuperSnake GTXG 20m cable, 50mm<sup>2</sup> (Std liner FE 1.0-1.6mm): SGTXG205CBL          SuperSnake GTXG 25m cable, 50mm<sup>2</sup> (Std liner FE 1.0-1.6mm): SGTXG255CBL          SuperSnake GTXW 10m cable, 50mm<sup>2</sup> (Std liner FE 1.0-1.6mm): SGTXW105CBL          SuperSnake GTXW 15m cable, 50mm<sup>2</sup> (Std liner FE 1.0-1.6mm): SGTXW155CBL          SuperSnake GTXW 20m cable, 50mm<sup>2</sup> (Std liner FE 1.0-1.6mm): SGTXW205CBL          SuperSnake GTXW 25m cable, 50mm<sup>2</sup> (Std liner FE 1.0-1.6mm): SGTXW255CBL          SuperSnake GTXW 10m cable, 70mm<sup>2</sup> (Std liner FE 1.0-1.6mm): SGTXW107CBL</p>
Description	subfeeder
Output 60% ED	350 A
Wire feed mechanism	2-roll
Wire feed speed	1...25 m/min
Wire recommendation, 25m Solid Fe/Ss	1.0...1.6 mm
Wire recommendation, 25m Al alloys	1.2...1.6 mm
Wire recommendation, 25m, FCW/MCW	1.2...1.6 mm
Cable diameter	50/70 mm <sup>2</sup>
Supply voltage	48 VDC
Protection class	IP23S
External dimensions without protective frame L x W x H	400 mm x 127 mm x 150 mm
External dimensions with protective frame L x W x H	682 mm x 174 mm x 159 mm